

NanoVIP® TWO™



EN NanoVIP® TWO™ is a modern, compact and powerful portable Power Quality analyzer for professional use that be used on single-phase, two-phase, three-phase balanced networks, low and medium voltage.

A long lasting battery (over 24h with one charge) and the huge data logging capacity (over 1 year) make it an absolute reliable and professional tool.

MEASUREMENT PRECISION, EASINESS OF USE

- ✓ LCD graphic display that allows wide flexibility in the (multilingual menu, waveforms, histograms, personalized pages, drawings, diagrams, pictures, etc.)
- ✓ PC Software NonoStudio dedicated through which you can make advanced analysis of the data stored on uSD
- ✓ 1 voltage measuring channel (1 phase + neutral) up to 600V CAT III, with the possibility to also measure the DC voltage, with the precision of the 0,25% + err.FS
- ✓ 1 current input with the possibility to also measure the DC current, with the precision of the 0,25% + err.FS
- ✓ Automatic verification of the correctness of the device connected to the network
Possibility to use flexible current probe up to 3000A or other captors with full scale set by the user
- ✓ High capacity batteries that allow a range of campaign more than 24 hours even in the absence of mains power; no country limit when connected to the network
- ✓ Calculation engine Powerful allowing besides the measuring of all standard electrical parameters (V I P Q A F PF THD% etc.) True RMS (TRMS): harmonics up to the 50th, dips, swells, microinterruptions and many other
- ✓ 20 alarms (generic, swells, dips and interruptions)
- ✓ Energy Measurement in 4 time zones (rates) set

NanoVIP® TWO™

CASE:

Dimensions	203x116x53mm
Material	ABS with self-extinguishing V0 grade
Protection class	IP30
Weight	580 g

DISPLAY:

Dimensions	68x68mm
Type	128x128 FSTN Negative dot matrix graphic LCD
Backlight	White LED
Languages	English - Spanish - Italian - German - French

KEYPAD:

Type	Membrane keypad with 10 double-function keys
------	--

POWER SUPPLY:

External power supply	wall-plug switching; input 100-240VAC $\pm 10\%$ 47-63Hz with interchangeable plug; output 7.5VDC - 12W
Battery pack	4 x AA NiMh 2100mAh
Duration of the battery charge	>24h (wireless off)

CONNECTABLE SYSTEMS:

Systems frequencies	50Hz – 60Hz – 400Hz
Single phase	✓
Two phase	✓
Three-phase, 3-wires, balanced	✓
Three-phase, 3-wires, unbalanced	-
4-phase, 4-wires, balanced	✓
4-phase, 4-wires, unbalanced	-

CONNECTIONS:

Voltages	Flexible cables L = 1.5m; 2.5mm ² - 36A; 1000V CAT III - 600V CAT IV with a 4mm, 90° protected blade plug connector, crocodile clips with a 45mm opening (for sections up to 32mm) and magnetic captors
Currents	Elcontrol Energy Net interchangeable amperometric sensors
Solar radiation	-
PT100	-
Anemometer	-
Transducers	-

FUNCTIONS:

Traditional electrical analysis	V, I, P, Q, S, F, PF, THD(V)%, THD(I)%, $\cos\phi$, ϕ , peaks, minimums, maximums, averages, max. demands, etc.
Neutral current	Measured
Three phase counters	kWh, kVArh, kVAh, both absorbed that generated
Counters for each single phase	kWh, kVArh, kVAh, both absorbed that generated
Cogeneration	✓
Waveforms	V & I
Harmonics	Values and histograms up to the 50 th order; up to 7 th at 400Hz
Sags	Dips, swells & interruptions
Transients	Overvoltages & overcurrents
Unbalance	-
Test EN 50160	✓
Inrush current	✓
DC measures	✓
K factor	Up to the 25 th order
Alarms	Displayed
Alarms log	5 at display

NanoVIP® TWO™

Tariff bands	4
Energy costs	✓
IEC 61724 network parameters	-
Test EN 82.25	-
OSU™ (One Shot UPS)	-
Measurement campaigns	unlimited, up to fill the memory card

MEASUREMENTS:

Sampling frequency	128 samples per cycle (adaptive in 40Hz-70Hz range) 16 samples per cycle at 400HZ
Data record rate	1 sec.
Data storage rate	User selectable: 1", 5", 3", 1', 5', 15'
Type of connections available	Three-phase (3 or 4 leads balanced), two-phase (2 leads), and single phase grid
Type of grid which can be connected	Low and medium voltage (LV and MV)

VOLTAGE (TRMS)

Channels	2 channels with common neutral
Input impedance	4 Mohm
Scales	2
Direct measurement	Phase-phase: 7-1000VAC 40-70Hz Phase-neutral: 5-600VAC 40-70Hz Aux: 5-1000VAC 40-70Hz, 10-1400VDC
Measurement with VT	Ratio: 1-60000 Maximum value which can be displayed: 20MV
Permanent overload	Phase-phase: 1200VAC Phase-neutral: 700VAC Aux: 1200VAC, 1700VDC
Sensitivity	5VAC Phase-neutral, 7VAC Phase-phase, 10VDC

CURRENT (TRMS)

Channels	1 channel
Input impedance	10KOhm
Scales	4
Measurement with current clamps	Ratio: 1-60000 Maximum value which can be displayed: 500KA
Sensitivity	0,2% of F.S.

POWERS

Single phase power	Values < 999 GW, Gvar, GVA
Total power	Values < 999 GW, Gvar, GVA

POWER COUNTERS

Maximum value before reset	99999999 kWh, kvarh, kVAh
----------------------------	---------------------------

ACCURACY

RMS voltages:	
Scale 1	$\pm 0.25\% + 0.1\%FS^{(2)}$ @ RMS V < 350VAC ⁽¹⁾
Scale 2	$\pm 0.25\% + 0.05\%FS^{(2)}$ @ RMS V > 350VAC ⁽¹⁾
RMS currents:	
Scale 1	$\pm 0.25\% + 0.1\%FS^{(2)}$ @ RMS I < 5% IN clamp ⁽¹⁾
Scale 2	$\pm 0.25\% + 0.05\%FS^{(2)}$ @ 5% < RMS I < 20% IN clamp ⁽¹⁾
Scale 3	$\pm 0.25\% + 0.05\%FS^{(2)}$ @ 20% < RMS I < 50% IN clamp ⁽¹⁾
Scale 4	$\pm 0.25\% + 0.05\%FS^{(2)}$ @ > 50% IN clamp ⁽¹⁾
Power	$\pm 0.5\% + 0.05\%FS^{(2)}$
Power Factor (PF)	$\pm 0.5^\circ$
Frequency	± 0.01 Hz (40-70Hz)
Active power count (kW)	Class 0.5

NanoVIP® TWO™

	Reactive power count (kVar) Class 1
HARMONIC ANALYSIS	Up to 50 th order Up to 7 th at 400Hz
ANALYSIS of EN50160 parameters	
Interruptions	>500mS
Dips	>500mS
Swells	>500mS
Transient ANALYSIS	
Swells and overcurrents	>150uS
Inrush current analysis	RMS continuous sampling every 2 periods – Duration 1, 2, 5, 10 sec.
COMMUNICATION:	
MRH™	-
Server mode	-
Connectable MRH™ clients	-
Client mode	-
Zigbee®	-
Maximum distance outdoor	600m (point to point)
Maximum distance indoor	60m (point to point)
Mesh network	-
Wireless to PC	-
USB	to PC
DATA STORAGE:	
Internal memory	64kB
External memory	Micro SD (2GB included)
OPERATING CONDITIONS:	
Operating temperature	-10 to +55 °C
Storage temperature	-20 to +85 °C
Relative humidity	Max 95%
Maximum altitude a.s.l. (600V CAT III)	2000 m
EC COMPLIANCE:	
Directives	93/68/EEC (Low Voltage Electrical Equipment); 89/336/EEC and 2004/108/EC (EMC - Electromagnetic Compatibility); 2006/95/EC - 72/23/EEC (LVD - Low Voltage Directive); 2002/95/EC (RoHS - Restriction of Hazardous Substances); 2002/96/EC and 2003/108/EC (WEEE - Waste Electrical and Electronic Equipment); IEC 61724
REFERENCE STANDARDS:	
Safety	EN 61010-1
Electromagnetic Compatibility (EMC)	EN 61326 EN 61326/A1 EN 61326/A2 EN 61326/A3
Temperature	IEC 60068-2-1 (Operating temperature) IEC 60068-2-2 (Storing temperature)
Vibrations	IEC 60068-2-6
Humidity	IEC 60068-2-30 (Humidity)
Overload	IEC 60947-1